

IP65 DMX RGB

EUROLITE LED IP T500 RGB 10mm 20°
Brilliant LED RGB outdoor color changer (IP65)

- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote
- Locking possibility at the mounting bracket
- Beam angle 20° or 40°



Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	14 W
Number of DMX control channels:	5
Protection grade:	IP 65
LED type:	10 mm
Number of LEDs:	114
Dimensions (LxWxH):	500 x 80 x 170 mm
Weight:	3 kg
No. 51914110	20°
No. 51914112	40°

DMX TCL RGB IP65

EUROLITE LED IP T500 TCL 9x3W 15°
LED RGB outdoor color changer with TCL LEDs (IP65)

- Color changer with 9 x 3 W LED
- Functions: static colors; automatic color change, 9 built-in programs and strobe effect with variable speed; Master/Slave
- Control in stand-alone mode and switch to DMX mode via optional IR remote
- Beam angle 15°



No. 51914113

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	30 W
Number of DMX channels:	3/4/5/6
DMX connection:	3-pin screwable connector plug
LED type:	3 W
Number of LEDs:	9
Beam angle:	15°
Dimensions (LxWxH):	500 x 80 x 100 mm
Weight:	3 kg

DMX BCL IP65 DAYLIGHT

EUROLITE LED IP T1000 BCL 12x5W 20°
Outdoor color changer (IP65) with 12 x 5 W BCL

- Equipped with 2in1 bicolor LEDs with white and amber
- Steplessly programmable color temperature and strobe effect
- Control in stand-alone mode and DMX programming via optional IR remote
- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave



No. 51913153

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	60 W/110 VA
Number of DMX control channels:	4
Protection grade:	IP 65
LED-type:	5-W BCL
Number of LEDs:	12
Beam angle:	20°
Dimensions (LxWxH):	1000 x 80 x 100 mm
Weight:	5 kg

NEW DMX HCL RGBAW + UV

EUROLITE LED IP T1000 HCL 9x12W
Ultra-flexible LED architectural spot (IP65) with 12 W HCL LEDs

- Equipped with 9 HCL LEDs in the colors red, green, blue, amber, white and UV
- Flicker-free projection
- For architectural lighting
- Fully convection cooled, no fans
- Different dimmer curves and dimmer speed (step response) adjustable



No. 51914121

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
Beam angle:	30°
LED type:	12 W HCL
Number of LEDs:	9
DMX control channels:	4/5/6/7/9/12
DMX512 connection:	3-pin screw connector
Flash-rate:	18 Hz
Dimensions (LxWxH):	584 x 190 x 101 mm
Weight:	4 kg

NEW DMX IP65 CW

EUROLITE LED IP T2000 WW
Versatile LED architectural lighting (IP65) with 5 W LEDs and 3800 K

- Special lenses offer a larger beam angle horizontally than vertically: 10°x40°
- Fully convection cooled, no fan
- Different dimmer curves adjustable
- Addressing and setting via Control Board with LED display and four operating buttons



No. 51914102

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
Protection grade:	IP 65
DMX control channels:	1/3
Flash-rate:	18 Hz
LED type:	5 W WW
Number of LEDs:	16
Color temperature:	3800 K
Dimensions (LxWxH):	999 x 184 x 95 mm
Weight:	7 kg

NEW DMX IP65 QCL RGBW

EUROLITE LED IP T2000 QCL
Versatile LED architectural lighting (IP65) with 15 W QCL LEDs by CREE

- Special lenses offer a larger beam angle horizontally than vertically: 10°x40°
- Fully convection cooled, no fan
- Different dimmer curves and dimmer speed (step response) adjustable
- Addressing and setting via Control Board with LED display and four operating buttons



No. 51914101

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	175 W
Protection grade:	IP 65
DMX control channels:	3/4/5/7/10
DMX512 connection:	3-pin screw connector
Flash-rate:	18 Hz
LED type:	15 W QCL (R,G,B,W)
Number of LEDs:	16
Dimensions (LxWxH):	999 x 184 x 95 mm
Weight:	7 kg