Mobile Light Systems





EUROLITE LED KLS-50 Compact Light Set DMX LED spotlight set with COB LEDs for mobile use

- Very powerful wide beams with 40° beam angle
- · Ultra-light and very small- ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 1 tricolor COB LED (RGB) per spot with 15 watts
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Supports QuickDMX for wireless reception of DMX512 signals



NEW DMX COB RGBW

EUROLITE LED KLS-40 Compact Light Set

DMX LED spotlight set with COB LEDs for mobile use

- · Ultra-light and ultra small ideally suited for mobile use
- RGBW color mixture per Spot
- · Control via DMX, sound or stand-alone mode
- · Convection cooling entirely via cooling ribs, no fans, particularly quiet during operation
- · Supports QuickDMX for wireless reception of DMX512 signals



NEW DMX QCL RGBW

EUROLITE LED KLS-30 Compact Light Set DMX LED spotlight set with 12 QCL LEDs for mobile use

- · Ultra-light and ultra small ideally suited for mobile use
- · Can be controlled via DMX, sound and stand-alone mode
- · Convection cooling entirely via cooling ribs, no fans, particularly quiet during operation
- 3 QCL LEDs with 4 watts each per spot (RGBW)
- Supports QuickDMX for wireless reception of DMX512 signals



EUROLITE FP-1 Foot Pedal Pedal switch for KLS

- · 4-pedal foot switch for convenient control of KLS light sets
- · Black out and freeze function
- · Sound control and auto program for color change



No. 42109711

EUROLITE Extension cord for FP-1 foot switch 10m

eurolite[®] www.eurolite.de

No. 42109601

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz ~
Power consumption:	65 W
DMX control channels:	2/3/4/5/12/15/20
DMX512 connection:	3-pin XLR
QuickDMX connection:	5-pin XLR
Sound control:	via built-in microphone
LED type:	COB 15 W
Number of LEDs:	4
Beam angle:	40°
TV spigot:	D = 28 mm
Dimensions (LxWxH):	720 x 90 x 235 mm
Weight:	4.3 kg



No. 42109605

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz \sim
Power consumption:	115 W
DMX control channels:	2/3/4/6/16/20/24
DMX512 connection:	3-pin XLR
QuickDMX connection:	5-pin XLR
Sound control:	via built-in microphone
LED type:	COB 30 W
Number of LEDs:	4
Beam angle:	12°
Dimensions (LxWxH):	450 x 120 x 185 mm
Weight:	3 kg



No. 42109603

Power supply:	100-240 V AC, 50/60 Hz ~
Power consumption:	50 W
DMX control channels:	2/3/4/6/16/20/24
DMX512 connection:	3-pin XLR
QuickDMX connection:	5-pin XLR
Sound control:	via built-in microphone
LED type:	QCL 4 W
Number of LEDs:	12
Beam angle:	24°
Dimensions (LxWxH):	450 x 120 x 185 mm
Weight:	3 kg



No. 42109710

Technical specifications: 1/0 x /20 x 25 mm

DIIIIelisiolis (LXWXII).	140 X 420 X 33 11111
Weight:	2 kg

