



# **MMX-602/SW**

Order No.: 20.2230

#### **EUR 289,00**

RRP\*

## **PRODUCTINFOS**

### Microphone line mixer,

6 channels.

- 6 stereo line inputs, 6 balanced mono microphone inputs, switchable
- Adjustable automatic talkover (-12 dB), switchable for channel 1 or channels 1+2
- Balance control for each stereo input channel
- 3-way equalizer
- 12 V phantom power can be activated as required
- LED VU meter, peak LED
- Master output and record output
- Output can be switched stereo/mono
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RS

# **TECHNICAL SPECIFICATIONS**

#### MMX-602/SW

No. of channels 6
No. of inputs 12

Mic input 1 mV/6.6 k $\Omega$ , 6 x 3-pole XLR, bal.

Line input 100 mV/10 k $\Omega$ , 6 x RCA L/R



#### MMX-602/SW

Master output  $\begin{array}{c} 1 \text{ V/600 } \Omega, \ 1 \text{ x RCA L/R} \\ 1 \text{ x 3-pole XLR L/R, bal.} \end{array}$ 

Record output 310 mV/600  $\Omega$ , 1 x RCA L/R

Headphones  $> 8 \Omega$ , 1 x 6.3 mm jack

Frequency range 20-20,000 Hz

THD 0.1%

S/N ratio 62 dB, unweighted

Equalizer bass  $\pm 12 \text{ dB/50 Hz}$ Equalizer midrange  $\pm 12 \text{ dB/1 kHz}$ Equalizer treble  $\pm 12 \text{ dB/10 kHz}$ Talkover -12 dB, manual

Power supply 230 V/50 Hz/12 VA

Mains voltage ~ 230 V

Mains frequency 50 Hz

Power consumption, operation 12 VA

Admiss. ambient temp. 0-40 °C

Width 482 mm

Height 47 mm

Depth 208 mm

Rack spaces, RS 1

Weight 2.8 kg

<sup>\*</sup> Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.