

# DMX Controllers Intelligent

DMX

#### **EUROLITE DMX LED Operator 1 controller**

Compact DMX controller for easy application

- 5 control channels only suitable for special LED-spots (RGB and TCL)
- Select color mode for choosing single colors
- · Internal programs
- · Auto mode for running all programs



#### **Technical specifications:** Power supply: 230 V AC, 50 Hz ~, via 12 V DC, 300 mA power unit included in the delivery Power consumption: Number of control channels: Sound-control: via built-in microphone DMX512 output: 3-pin XLR connector Dimensions (LxWxH): 220 x 145 x 65 mm Weight:



DMX

#### **EUROLITE DMX LED Operator 2 controller**

Compact DMX controller for easy application

- . 8 control channels suitable for all LED-spots with RGBA and/or RGBW
- · Select color mode for choosing single colors
- · 2 internal programs
- Auto mode for running all programs
- Button for a smoke machine

No. 70064502

Technical specific	cations:
Power supply:	230 V AC, 50 Hz ∼,
	via 12 V DC, 300 mA power unit included in the delivery
Power consumption:	4 W
Number of control channe	els: 8
Sound-control:	via built-in microphone
DMX512 output:	3-pin XLR connector
Dimensions (LxWxH):	265 x 165 x 55 mm
Weight:	1 kg



DMX

## **EUROLITE DMX LED Operator 6 controller**

DMX controller for RGBWA+UV LED spots

- 6 DMX channels (red/green/blue/white/amber/UV) can be controlled per unit
- Sequence of white and amber function freely selectable per unit
- 6 trigger buttons for direct color selection
- 18 trigger buttons for preset color chases

No. 70064506

|--|

Power supply:	100-240 V AC, 50/60 Hz ~
	via power unit included in the delivery
Power consumption:	4 W
Number of control channels:	6 x 6
Sound-control:	via built-in microphone
DMX512 output:	3-pin XLR connector
Dimensions (LxWxH):	150 x 400 x 70 mm
Weight:	1.5 kg



### **EUROLITE DMX LED Operator 4 controller**

Compact DMX controller for easy application

- · Easy DMX512 control
- · Designed for RGB spots with 5-channel mode
- · Controls 4 LED parcans or 1 matching KLS system or 1 LED Bar (RGB 252/10)
- Additional control of 1 smoke machine



No. 70064509



No. 70064504

#### **Technical specifications:**

Power supply:	230 V AC, 50 Hz ∼,
via 9-12 V DC, 300 mA power unit included in the delivery	
Power consumption:	4 W
Number of control channels:	50
Sound-control:	via built-in microphone or RCA input
DMX512 output:	3-pin XLR connector
Dimensions (LxWxH):	320 x 190 x 60 mm
Weight:	1.4 kg

