

ACTIVE

OMNITRONIC ACS-510 Active system

Active PA system with 3-channel mixer, 510 watts

- Flexible use: mono, 2.1 or stereo setup with 2 systems linked together
- Smart click mechanism allows stacking satellites in mono mode without cables
- 2-channel amplifier system with 1 x 350 W for subwoofer and 2 x 80 W or 1 x 160 W for satellites
- Integrated 3-channel mic/line mixer
- Low-resonance polystyrene enclosure (HIPS) with bassreflex port
- Total weight just 17.7 kg
- Subwoofer with convenient transport compartment for satellites
- Set incl. 2 speaker tripods for 2.1 setup



No. 11038860

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz ~
Power consumption:	100 W (1/8 power)
Subwoofer:	
Power output:	350 W at 4 ohms 2 x 80 W at 8 ohms
Woofers:	25 cm (10")
Max. SPL (10 % THD):	120 dB
Max. SPL (Peak):	123 dB
Frequency range:	50 - 160 Hz
Dimensions (LxWxH):	405 x 345 x 460 mm
Weight:	14 kg
1 satellite:	
Power output:	80 W at 8 ohms
Midrange speaker:	12 cm (4.75")
Tweeter:	2.5 cm (1")
Max. SPL (10 % THD):	120 dB
Max. SPL (Peak):	123 dB
Frequency range:	155 Hz - 22 kHz
Dispersion angle (HxV):	90° x 10°/-45°
Dimensions (LxWxH):	109 x 142 x 228 mm
Weight:	2 kg
2 satellites:	
Power output:	160 W at 8 ohms
Midrange speaker:	2 x 12 cm (4.75")
Tweeter:	2 x 2.5 cm (1")
Max. SPL (10 % THD):	125 dB
Max. SPL (Peak):	130 dB
Frequency range:	155 Hz - 19 kHz
Dispersion angle (HxV):	90° x 60°
Dimensions (LxWxH):	109 x 142 x 456 mm
Weight:	4 kg
Inputs:	
Mic/Line 1:	combination XLR/6.3 mm jack
Mic/Line 2:	2 x combination XLR/6.3 mm jack
Line 3:	RCA L/R, 3.5 mm jack
Speaker outputs:	2 x 6.3 mm jack
Link:	6.3 mm jack
Rec/Thru:	2 x 6.3 mm jack