



OMNITRONIC C 2x

Speaker pair

- Woofer: 10 cm (4") to 20 cm (8") - dome tweeter: 2.5 cm (1")
- Robust plastic housing (ABS)
- Movable mounting bracket for ceiling or wall installation
- Packed as a pair (2 pieces)
- Clear and powerful sound

No. 11036710.....	C-40, 10 cm black
No. 11036711.....	C-40, 10 cm white
No. 11036714.....	C-50, 13 cm black
No. 11036715.....	C-50, 13 cm white
No. 11036718.....	C-60, 16 cm black
No. 11036719.....	C-60, 16 cm white
No. 11036722.....	C-80, 20 cm black
No. 11036723.....	C-80, 20 cm white

Technical specifications:

Device:	C-40 passive	C-50 passive	C-60 passive	C-80 passive
Color:	black/white	black/white	black/white	black/white
Rated power:	35 W RMS	40 W RMS	50 W RMS	85 W RMS
Program power:	75 W	80 W	100 W	125 W
Components:	10 cm woofer (4"), 2.5 cm tweeter (1")	13 cm woofer (5"), 2.5 cm tweeter (1")	16.5 cm woofer (6.5"), 2.5 cm tweeter (1")	20 cm woofer (8"), 2.5 cm tweeter (1")
Connections:	2-pole terminal	2-pole terminal	2-pole terminal	2-pole terminal
Sensitivity:	89 dB (1 W, 1 m)	89 dB (1 W, 1 m)	89 dB (1 W, 1 m)	90 dB (1 W, 1 m)
Impedance:	8 ohms	8 ohms	8 ohms	8 ohms
Frequency range:	50 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 20 kHz
Dimensions (H x W x D):	215 x 160 x 155 mm	230 x 180 x 172 mm	285 x 205 x 180 mm	360 x 270 x 240 mm
Weight:	1.5 kg	2.2 kg	3.5 kg	6 kg



OMNITRONIC DH titanium 2x

Speaker pair - 2-way system

- Polypropylene woofer: 13/16.5/20 cm (5/6.5/8")
- Dome tweeter: 2 cm (0.75") and 2.5 cm (1", DH-80) with horn front attachment
- Highly efficient bass-reflex system (DH-60/80)
- Well-balanced and clear sound, even with demanding music
- Mounting bracket for ceiling or wall installation
- Clear and powerful sound

Technical specifications:

Device:	DH-40 passive	DH-60 passive	DH-80 passive
Rated power:	35 W RMS	40 W RMS	85 W RMS
Program power:	70 W	80 W	170 W
Components:	13 cm woofer (5"), 2 cm horn (0.75")	13 cm woofer (5"), 2.5 cm tweeter (1")	20 cm woofer (8"), 2.5 cm horn (1")
Connections:	2-pole terminal	2-pole terminal	2-pole terminal
Max. SPL:	103 dB	89 dB (1 W, 1 m)	116 dB
Impedance:	8 ohms	8 ohms	8 ohms
Frequency range:	60 Hz - 18 kHz	50 Hz - 20 kHz	45 Hz - 20 kHz
Dimensions (H x W x D):	247 x 158 x 152 mm	230 x 180 x 166 mm	420 x 253 x 249 mm
Weight (piece):	2.3 kg	2.2 kg	6 kg

No. 11036756.....	DH-40, 10cm
No. 11036772.....	DH-60, 16cm
No. 11036791.....	DH-80, 20cm



OMNITRONIC LI MK2 2-way top

Dedicated PA speaker system

- Higher quality than common mini speakers
- Matches the PAS series by OMNITRONIC
- 10/16.5 cm (4/6.5") bass speaker and 25 mm (1") horn tweeter, with PTC tweeter protection
- Attractive trapezoidal cabinet made of 8/12 mm plywood
- For high-class background PA applications
- U-shape mounting brackets included

Technical specifications:

Device:	LI-204	LI-206
Rated power:	30 W RMS	50 W RMS
Program power:	60 W	100 W
Components:	10 cm woofer (4"), 2.5 cm calotte (1")	16.5 cm woofer (6.5"), 2.5 cm calotte (1")
Connections:	2-pole plug-in screw terminal	2-pole plug-in screw terminal
Sensitivity:	87 dB (1 W, 1 m)	89 dB (1 W, 1 m)
Max. SPL:	105 dB (1 m)	109 dB (1 m)
Impedance:	16 ohms	16 ohms
Frequency range:	100 Hz - 20 kHz	80 Hz - 20 kHz
Crossover frequency:	3500 kHz	2200 kHz
Dispersion angle (H):	120°	120°
Dimensions (H x W x D):	245 x 152 x 136 mm	320 x 200 x 200 mm
Weight:	2.7 kg	4.4 kg

No. 11038981.....	LI-204, black
No. 11038985.....	LI-204, white
No. 11038983.....	LI-206, black
No. 11038987.....	LI-206, white